

4806

WIRE BRAID AIR HOSE - WIRE REINFORCED



CONSTRUCTION: Tube is nitrile, ARPM Class B, smooth and black. Cover is NBR/PVC, fabric impression and pin-pricked. Reinforcement is one braid of wire.

TEMPERATURE: -40°F (-40°C) to +212°F (+100°C)

BRANDING: Jason logo 4806 WIRE BRAID AIR WP (PSI) (BAR)

STANDARD LENGTHS: 50 ft. and 100 ft., all sizes.

DESIGN FACTOR: 4:1

APPLICATION: For heavy duty air supply in mining, quarries, construction, industrial air placement, sand-blasting and heavy duty equipment rental.

FEATURES:

- Oil mist resistant tube
- Bright yellow non-marking cover
- High working pressure
- Heavy duty cover and wire braid reinforcement for maximum durability

Part Number	I.D.		O.D.		Reinf. Braid	Max. W.P. @ 68° F		Vacuum @ 68°F	Weight		Minimum Bend Radius		Standard Lengths	
	inch	mm	inch	mm		PSI	BAR		lb./ft.	KG/m	inch	mm	feet	meter
4806-0075-050	3/4	19.05	1.24	31.60	1	600	41.37	n/a	0.79	0.53	8.30	210.00	50	15.2
4806-0075-100	3/4	19.05	1.24	31.60	1	600	41.37	n/a	0.79	0.53	8.30	210.00	100	30.5
4806-0100-050	1	25.40	1.24	31.6	1	600	41.37	n/a	1.04	0.70	11.0	280.0	50	15.2
4806-0100-100	1	25.40	1.24	31.6	1	600	41.37	n/a	1.04	0.70	11.0	280.0	100	30.5
4806-0150-050	1-1/2	38.10	2.06	52.2	1	600	41.37	n/a	1.75	1.17	16.5	420.0	50	15.2
4806-0150-100	1-1/2	38.10	2.06	52.2	1	600	41.37	n/a	1.75	1.17	16.5	420.0	100	30.5
4806-0200-050	2	50.80	2.67	67.90	1	600	41.37	n/a	2.33	1.56	22.00	560.00	50	15.2
4806-0200-100	2	50.80	2.67	67.90	1	600	41.37	n/a	2.33	1.56	22.00	560.00	100	30.5
4806-0300-050	3	76.20	3.78	96.00	1	600	41.37	n/a	4.08	2.74	33.10	840.00	50	15.2
4806-0300-100	3	76.20	3.78	96.00	1	600	41.37	n/a	4.08	2.74	33.10	840.00	100	30.5

Working pressure (W.P.) is temperature dependent. See the General Information section Table II - Pressure Re-Rating for increased Temperatures (Page 11) for more information.

All sizes may not be stocked in all locations. Check with customer service for availability.
We disclaim any liability for use of our products in applications other than which they are designed.