

Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
4806-0075	Wire Braid Air	3/4"	12XX-12	1-piece	34.3	1.350	Full	31	3.3	8/1/23
4806-0100	Wire Braid Air	1"	12XX-16	1-piece	43.4	1.709	Full	39	4.4	8/1/23
4816-0050	Steam	1/2"	12XX-08	1-piece	25.9	1.020	Full	23	2.9	8/1/23
4816-0075	Steam	3/4"	12XX-12	1-piece	32.5	1.280	Full	31	1.5	8/1/23
4816-0100	Steam	1"	12XX-16	1-piece	40.8	1.606	Full	39	1.8	8/1/23
4183-0050	Wash Down	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	1.2	8/1/23
4183-0075	Wash Down	3/4"	12XX-12	1-piece	32.6	1.283	Full	31	1.6	8/1/23
4183-0100	Wash Down	1"	12XX-16	1-piece	41.0	1.614	Full	39	2.0	8/1/23
4183-0125	Wash Down	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	0.3	8/1/23
5010-03	SAE 100R1	3/16"	12XX-03	1-piece	14.2	0.559	Full	12	2.2	8/1/23
5010-04	SAE 100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	0.6	8/1/23
5010-05	SAE 100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	2.3	8/1/23
5010-06	SAE 100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	2.2	8/1/23
5010-08	SAE 100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	1.2	8/1/23
5010-10	SAE 100R1	5/8"	12XX-10	1-piece	27.2	1.071	Full	27	0.2	8/1/23
5010-12	SAE 100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	0.9	8/1/23
5010-16	SAE 100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5010-20	SAE 100R1	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	0.3	8/1/23
5011-04	SAE 100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	0.6	8/1/23
5011-05	SAE 100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	2.3	8/1/23
5011-06	SAE 100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	2.2	8/1/23
5011-08	SAE 100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	1.2	8/1/23
5011-12	SAE 100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	0.9	8/1/23
5011-16	SAE 100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5012-03	SAE 100R1	3/16"	12XX-03	1-piece	14.2	0.559	Full	12	2.2	8/1/23
5012-04	SAE 100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	0.6	8/1/23
5012-05	SAE 100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	2.3	8/1/23
5012-06	SAE 100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	2.2	8/1/23
5012-08	SAE 100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	1.2	8/1/23
5012-10	SAE 100R1	5/8"	12XX-10	1-piece	27.2	1.071	Full	27	0.2	8/1/23
5012-12	SAE 100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	0.9	8/1/23
5012-16	SAE 100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5012-20	SAE 100R1	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	0.3	8/1/23
5020-04	SAE 100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5020-05	SAE 100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	0.3	8/1/23
5020-06	SAE 100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	3.2	8/1/23
5020-08	SAE 100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	2.2	8/1/23
5020-10	SAE 100R2	5/8"	12XX-10	1-piece	28.2	1.110	Full	27	1.2	8/1/23
5020-12	SAE 100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	1.9	8/1/23
5020-16	SAE 100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	2.6	8/1/23
5020-20	SAE 100R2	1-1/4"	12XX-20	1-piece	51.3	2.020	Full	50	1.3	8/1/23
5021-04	SAE 100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5021-05	SAE 100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	0.3	8/1/23
5021-06	SAE 100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	3.2	8/1/23
5021-08	SAE 100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	2.2	8/1/23
5021-12	SAE 100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	1.9	8/1/23
5021-16	SAE 100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	2.6	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to +/- 0.005" (+/- 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.



Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
5022-04	SAE 100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5022-05	SAE 100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	0.3	8/1/23
5022-06	SAE 100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	3.2	8/1/23
5022-08	SAE 100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	2.2	8/1/23
5022-10	SAE 100R2	5/8"	12XX-10	1-piece	28.2	1.110	Full	27	1.2	8/1/23
5022-12	SAE 100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	1.9	8/1/23
5022-16	SAE 100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	2.6	8/1/23
5022-20	SAE 100R2	1-1/4"	12XX-20	1-piece	51.3	2.020	Full	50	1.3	8/1/23
5040-12	SAE 100R4	3/4"	12XX-12	1-piece	33.7	1.325	Full	31	2.7	8/1/23
5040-16	SAE 100R4	1"	12XX-16	1-piece	40.6	1.600	Full	39	1.6	8/1/23
5040-20	SAE 100R4	1-1/4"	12XX-20	1-piece	48.3	1.900	Full	45	3.3	8/1/23
5100-04	Hot Air/Oil	1/4"	12XX-04	1-piece	16.3	0.640	Full	16	0.3	8/1/23
5100-06	Hot Air/Oil	3/8"	12XX-06	1-piece	19.6	0.770	Full	19	0.6	8/1/23
5100-08	Hot Air/Oil	1/2"	12XX-08	1-piece	23.1	0.910	Full	23	0.1	8/1/23
5120-06	SAE 100R12	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	1.4	8/1/23
5120-08	SAE 100R12	1/2"	40XX-08	1-piece	28.2	1.110	Full	27	1.2	8/1/23
5120-10	SAE 100R12	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	0.2	8/1/23
5120-12	SAE 100R12	3/4"	40XX-12	1-piece	34.6	1.362	Full	34	0.6	8/1/23
5120-16	SAE 100R12	1"	40XX-16	1-piece	43.3	1.705	Full	39	4.3	8/1/23
5120-20	SAE 100R12	1-1/4"	40XX-20	1-piece	51.7	2.035	Full	50	1.7	8/1/23
5122-06	SAE 100R12	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	1.4	8/1/23
5122-08	SAE 100R12	1/2"	40XX-08	1-piece	28.2	1.110	Full	27	1.2	8/1/23
5122-10	SAE 100R12	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	0.2	8/1/23
5122-12	SAE 100R12	3/4"	40XX-12	1-piece	34.6	1.362	Full	34	0.6	8/1/23
5122-16	SAE 100R12	1"	40XX-16	1-piece	43.3	1.705	Full	39	4.3	8/1/23
5122-20	SAE 100R12	1-1/4"	40XX-20	1-piece	51.7	2.035	Full	50	1.7	8/1/23
5152-06	SAE 100R15	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	1.4	8/1/23
5152-08	SAE 100R15	1/2"	40XX-08	1-piece	28.7	1.130	Full	27	1.7	8/1/23
5152-10	SAE 100R15	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	0.2	8/1/23
5160-04	SAE 100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	0.8	8/1/23
5160-05	SAE 100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	2.5	8/1/23
5160-06	SAE 100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	2.1	8/1/23
5160-08	SAE 100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	1.5	8/1/23
5160-10	SAE 100R16	5/8"	12XX-10	1-piece	27.5	1.083	Full	27	0.5	8/1/23
5160-12	SAE 100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	1.1	8/1/23
5160-16	SAE 100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5161-04	SAE 100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	0.8	8/1/23
5161-05	SAE 100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	2.5	8/1/23
5161-06	SAE 100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	2.1	8/1/23
5161-08	SAE 100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	1.5	8/1/23
5161-12	SAE 100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	1.1	8/1/23
5161-16	SAE 100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to +/- 0.005" (+/- 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.



Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
5162-04	SAE 100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	0.8	8/1/23
5162-05	SAE 100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	2.5	8/1/23
5162-06	SAE 100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	2.1	8/1/23
5162-08	SAE 100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	1.5	8/1/23
5162-10	SAE 100R16	5/8"	12XX-10	1-piece	27.5	1.083	Full	27	0.5	8/1/23
5162-12	SAE 100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	1.1	8/1/23
5162-16	SAE 100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5170-04	SAE 100R17	1/4"	12XX-04	1-piece	16	0.630	Full	14	2	8/1/23
5170-05	SAE 100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5170-06	SAE 100R17	3/8"	12XX-06	1-piece	20	0.787	Full	19	1	8/1/23
5170-08	SAE 100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	0.5	8/1/23
5170-10	SAE 100R17	5/8"	12XX-10	1-piece	27.7	1.091	Full	27	0.7	8/1/23
5170-12	SAE 100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	1.2	8/1/23
5170-16	SAE 100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	2.1	8/1/23
5171-04	SAE 100R17	1/4"	12XX-04	1-piece	16.0	0.630	Full	14	2	8/1/23
5171-05	SAE 100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5171-06	SAE 100R17	3/8"	12XX06-	1-piece	20.0	0.787	Full	19	1	8/1/23
5171-08	SAE 100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	0.5	8/1/23
5171-12	SAE 100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	1.2	8/1/23
5171-16	SAE 100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	2.1	8/1/23
5172-04	SAE 100R17	1/4"	12XX-04	1-piece	16.0	0.630	Full	12	4	8/1/23
5172-05	SAE 100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5172-06	SAE 100R17	3/8"	12XX-06	1-piece	20.0	0.787	Full	19	1	8/1/23
5172-08	SAE 100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	0.5	8/1/23
5172-10	SAE 100R17	5/8"	12XX-10	1-piece	27.7	1.091	Full	27	0.7	8/1/23
5172-12	SAE 100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	1.2	8/1/23
5172-16	SAE 100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	2.1	8/1/23
5192-04	SAE 100R19	1/4"	12XX-04	1-piece	16.9	0.665	Full	16	0.9	8/1/23
5192-06	SAE 100R19	3/8"	12XX-06	1-piece	21.0	0.827	Full	19	2	8/1/23
5192-08	SAE 100R19	1/2"	12XX-08	1-piece	24.8	0.976	Full	23	1.8	8/1/23
5192-10	SAE 100R19	5/8"	12XX-10	1-piece	27.8	1.094	Full	27	0.8	8/1/23
5192-12	SAE 100R19	3/4"	12XX-12	1-piece	31.8	1.252	Full	31	0.8	8/1/23
5192-16	SAE 100R19	1"	12XX-16	1-piece	40.6	1.598	Full	39	1.6	8/1/23
5201-08	N/A	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	1.5	8/1/23
5220-04	Jack Line	1/4"	1220L-0404	1-piece	17.6	0.693	Full	16	1.6	8/1/23
5220-06	Jack Line	3/8"	1220L-0606	1-piece	22.2	0.874	Full	19	3.2	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to +/- 0.005" (+/- 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.

