

Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
4806-0075	Wire Braid Air	3/4"	12XX-12	1-piece	34.3	1.350	Full	31	N/A	8/1/23
4806-0100	Wire Braid Air	1"	12XX-16	1-piece	43.4	1.709	Full	39	N/A	8/1/23
4806-0150	Wire Braid Air	1-1/2"	12XX-24	1-piece	58.3	2.295	Full	57	N/A	8/1/23
4806-0200	Wire Braid Air	2"	12XX-32	1-piece	70.4	2.772	Full	69	N/A	8/1/23
4816-0075	Steam	3/4"	12XX-12	1-piece	32.5	1.280	Full	31	N/A	8/1/23
4816-0100	Steam	1"	12XX-16	1-piece	40.8	1.606	Full	39	N/A	8/1/23
4816-0125	Steam	1-1/4"	12XX-20	1-piece	48.6	1.913	Full	45	N/A	8/1/23
4816-0150	Steam	1-1/2"	12XX-24	1-piece	61.3	2.413	Full	57	N/A	8/1/23
4816-0200	Steam	2"	12XX-32	1-piece	72.6	2.858	Full	69	N/A	8/1/23
4183-0050	Wash Down	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	N/A	8/1/23
4183-0075	Wash Down	3/4"	12XX-12	1-piece	32.6	1.283	Full	31	N/A	8/1/23
4183-0100	Wash Down	1"	12XX-16	1-piece	41.0	1.614	Full	39	N/A	8/1/23
4183-0125	Wash Down	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	N/A	8/1/23
4183-0150	Wash Down	1-1/2"	12XX-24	1-piece	58.4	2.299	Full	57	N/A	8/1/23
4183-0200	Wash Down	2"	12XX-32	1-piece	69.7	2.744	Full	69	N/A	8/1/23
5010-03	SAE100R1	3/16"	12XX-03	1-piece	14.2	0.559	Full	12	N/A	8/1/23
5010-04	SAE100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	N/A	8/1/23
5010-05	SAE100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	N/A	8/1/23
5010-06	SAE100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	N/A	8/1/23
5010-08	SAE100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	N/A	8/1/23
5010-10	SAE100R1	5/8"	12XX-10	1-piece	27.2	1.071	Full	27	N/A	8/1/23
5010-12	SAE100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	N/A	8/1/23
5010-16	SAE100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5010-20	SAE100R1	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	N/A	8/1/23
5010-24	SAE100R1	1-1/2"	12XX-24	1-piece	58.4	2.299	Full	57	N/A	8/1/23
5010-32	SAE100R1	2"	12XX-32	1-piece	69.7	2.744	Full	63	N/A	8/1/23
5011-04	SAE100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	N/A	8/1/23
5011-05	SAE100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	N/A	8/1/23
5011-06	SAE100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	N/A	8/1/23
5011-08	SAE100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	N/A	8/1/23
5011-12	SAE100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	N/A	8/1/23
5011-16	SAE100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5012-03	SAE100R1	3/16"	12XX-03	1-piece	14.2	0.559	Full	12	N/A	8/1/23
5012-04	SAE100R1	1/4"	12XX-04	1-piece	16.6	0.654	Full	16	N/A	8/1/23
5012-05	SAE100R1	5/16"	12XX-05	1-piece	18.3	0.720	Full	16	N/A	8/1/23
5012-06	SAE100R1	3/8"	12XX-06	1-piece	21.2	0.835	Full	19	N/A	8/1/23
5012-08	SAE100R1	1/2"	12XX-08	1-piece	24.2	0.953	Full	23	N/A	8/1/23
5012-10	SAE100R1	5/8"	12XX-10	1-piece	27.2	1.071	Full	27	N/A	8/1/23
5012-12	SAE100R1	3/4"	12XX-12	1-piece	31.9	1.256	Full	31	N/A	8/1/23
5012-16	SAE100R1	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5012-20	SAE100R1	1-1/4"	12XX-20	1-piece	50.3	1.980	Full	50	N/A	8/1/23
5012-24	SAE100R1	1-1/2"	12XX-24	1-piece	58.4	2.299	Full	57	N/A	8/1/23
5012-32	SAE100R1	2"	12XX-32	1-piece	69.7	2.744	Full	63	N/A	8/1/23
5020-04	SAE100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5020-05	SAE100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	N/A	8/1/23
5020-06	SAE100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	N/A	8/1/23
5020-08	SAE100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	N/A	8/1/23
5020-10	SAE100R2	5/8"	12XX-10	1-piece	28.2	1.110	Full	27	N/A	8/1/23
5020-12	SAE100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	N/A	8/1/23
5020-16	SAE100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	N/A	8/1/23
5020-20	SAE100R2	1-1/4"	12XX-20	1-piece	51.3	2.020	Full	50	N/A	8/1/23
5020-24	SAE100R2	1-1/2"	12XX-24	1-piece	59.4	2.339	Full	57	N/A	8/1/23
5020-32	SAE100R2	2"	12XX-32	1-piece	70.7	2.783	Full	69	N/A	8/1/23
5021-04	SAE100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5021-05	SAE100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	N/A	8/1/23
5021-06	SAE100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	N/A	8/1/23
5021-08	SAE100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	N/A	8/1/23
5021-12	SAE100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	N/A	8/1/23
5021-16	SAE100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	N/A	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to +/- 0.005" (+/- 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.



Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
5022-04	SAE100R2	1/4"	12XX-04	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5022-05	SAE100R2	5/16"	12XX-05	1-piece	19.3	0.760	Full	19	N/A	8/1/23
5022-06	SAE100R2	3/8"	12XX-06	1-piece	22.2	0.874	Full	19	N/A	8/1/23
5022-08	SAE100R2	1/2"	12XX-08	1-piece	25.2	0.992	Full	23	N/A	8/1/23
5022-10	SAE100R2	5/8"	12XX-10	1-piece	28.2	1.110	Full	27	N/A	8/1/23
5022-12	SAE100R2	3/4"	12XX-12	1-piece	32.9	1.295	Full	31	N/A	8/1/23
5022-16	SAE100R2	1"	12XX-16	1-piece	41.6	1.638	Full	39	N/A	8/1/23
5022-20	SAE100R2	1-1/4"	12XX-20	1-piece	51.3	2.020	Full	50	N/A	8/1/23
5022-24	SAE100R2	1-1/2"	12XX-24	1-piece	59.4	2.339	Full	57	N/A	8/1/23
5022-32	SAE100R2	2"	12XX-32	1-piece	70.7	2.783	Full	69	N/A	8/1/23
5040-12	SAE 100R4	3/4"	12XX-12	1-piece	33.7	1.325	Full	31	N/A	8/1/23
5040-16	SAE 100R4	1"	12XX-16	1-piece	40.6	1.600	Full	39	N/A	8/1/23
5040-20	SAE 100R4	1-1/4"	12XX-20	1-piece	48.3	1.900	Full	45	N/A	8/1/23
5040-24	SAE 100R4	1-1/2"	12XX-24	1-piece	57.2	2.250	Full	57	N/A	8/1/23
5040-32	SAE 100R4	2"	12XX-32	1-piece	69.2	2.725	Full	69	N/A	8/1/23
5100-04	HOT AIR/OIL	1/4"	12XX-04	1-piece	16.3	0.640	Full	16	N/A	8/1/23
5100-06	HOT AIR/OIL	3/8"	12XX-06	1-piece	19.6	0.770	Full	19	N/A	8/1/23
5100-08	HOT AIR/OIL	1/2"	12XX-08	1-piece	23.1	0.910	Full	23	N/A	8/1/23
5120-06	SAE100R12	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	N/A	8/1/23
5120-08	SAE100R12	1/2"	40XX-08	1-piece	28.2	1.110	Full	27	N/A	8/1/23
5120-10	SAE100R12	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	N/A	8/1/23
5120-12	SAE100R12	3/4"	40XX-12	1-piece	34.6	1.362	Full	34	N/A	8/1/23
5120-16	SAE100R12	1"	40XX-16	1-piece	43.3	1.705	Full	39	N/A	8/1/23
5120-20	SAE100R12	1-1/4"	40XX-20	1-piece	51.7	2.035	Full	50	N/A	8/1/23
5120-24	SAE100R12	1-1/2"	40XX-24	1-piece	58.4	2.299	Full	57	N/A	8/1/23
5122-06	SAE100R12	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	N/A	8/1/23
5122-08	SAE100R12	1/2"	40XX-08	1-piece	28.2	1.110	Full	27	N/A	8/1/23
5122-10	SAE100R12	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	N/A	8/1/23
5122-12	SAE100R12	3/4"	40XX-12	1-piece	34.6	1.362	Full	34	N/A	8/1/23
5122-16	SAE100R12	1"	40XX-16	1-piece	43.3	1.705	Full	39	N/A	8/1/23
5122-20	SAE100R12	1-1/4"	40XX-20	1-piece	51.7	2.035	Full	50	N/A	8/1/23
5122-24	SAE100R12	1-1/2"	40XX-24	1-piece	58.4	2.299	Full	57	N/A	8/1/23
5130-12	SAE100R13	3/4"	60XX-12	1-piece	35.3	1.390	Full	34	N/A	8/1/23
5130-16	SAE100R13	1"	60XX-16	1-piece	43.2	1.701	Full	39	N/A	8/1/23
5130-20	SAE100R13	1-1/4"	60XX-20	1-piece	53.6	2.110	Full	50	N/A	8/1/23
5132-12	SAE100R13	3/4"	60XX-12	1-piece	35.3	1.390	Full	34	N/A	8/1/23
5132-16	SAE100R13	1"	60XX-16	1-piece	43.2	1.701	Full	39	N/A	8/1/23
5132-20	SAE100R13	1-1/4"	60XX-20	1-piece	54.6	2.150	Full	50	N/A	8/1/23
5152-06	SAE 100R15	3/8"	40XX-06	1-piece	24.4	0.961	Full	23	N/A	8/1/23
5152-08	SAE 100R15	1/2"	40XX-08	1-piece	28.2	1.130	Full	27	N/A	8/1/23
5152-10	SAE 100R15	5/8"	40XX-10	1-piece	31.2	1.228	Full	31	N/A	8/1/23
5152-12	SAE100R15	3/4"	60XX-12	1-piece	35.3	1.390	Full	34	N/A	8/1/23
5152-16	SAE100R15	1"	60XX-16	1-piece	43.2	1.701	Full	39	N/A	8/1/23
5152-20	SAE100R15	1-1/4"	60XX-20	1-piece	54.6	2.150	Full	50	N/A	8/1/23
5160-04	SAE100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	N/A	8/1/23
5160-05	SAE100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	N/A	8/1/23
5160-06	SAE100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	N/A	8/1/23
5160-08	SAE100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	N/A	8/1/23
5160-10	SAE100R16	5/8"	12XX-10	1-piece	27.5	1.083	Full	27	N/A	8/1/23
5160-12	SAE100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	N/A	8/1/23
5160-16	SAE100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to $\pm 0.005"$ (± 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.



Hose Series	Hose Type	Hose Size	Coupling Series	Coupling Type	Crimp Diameter (mm)	Crimp Diameter (inch)	Crimp Position	Die	Approx. Scale Setting	Revision Date
5161-04	SAE100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	N/A	8/1/23
5161-05	SAE100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	N/A	8/1/23
5161-06	SAE100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	N/A	8/1/23
5161-08	SAE100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	N/A	8/1/23
5161-12	SAE100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	N/A	8/1/23
5161-16	SAE100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5162-04	SAE100R16	1/4"	12XX-04	1-piece	16.8	0.661	Full	16	N/A	8/1/23
5162-05	SAE100R16	5/16"	12XX-05	1-piece	18.5	0.728	Full	16	N/A	8/1/23
5162-06	SAE100R16	3/8"	12XX-06	1-piece	21.1	0.831	Full	19	N/A	8/1/23
5162-08	SAE100R16	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	N/A	8/1/23
5162-10	SAE100R16	5/8"	12XX-10	1-piece	27.5	1.083	Full	27	N/A	8/1/23
5162-12	SAE100R16	3/4"	12XX-12	1-piece	32.1	1.264	Full	31	N/A	8/1/23
5162-16	SAE100R16	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5170-04	SAE100R17	1/4"	12XX-04	1-piece	16.0	0.630	Full	14	N/A	8/1/23
5170-05	SAE100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5170-06	SAE100R17	3/8"	12XX-06	1-piece	20.0	0.787	Full	19	N/A	8/1/23
5170-08	SAE100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	N/A	8/1/23
5170-10	SAE100R17	5/8"	12XX-10	1-piece	27.7	1.091	Full	27	N/A	8/1/23
5170-12	SAE100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	N/A	8/1/23
5170-16	SAE100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	N/A	8/1/23
5171-04	SAE100R17	1/4"	12XX-04	1-piece	16.0	0.630	Full	14	N/A	8/1/23
5171-05	SAE100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5171-06	SAE100R17	3/8"	12XX-06	1-piece	20.0	0.787	Full	19	N/A	8/1/23
5171-08	SAE100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	N/A	8/1/23
5171-12	SAE100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	N/A	8/1/23
5171-16	SAE100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	N/A	8/1/23
5172-04	SAE100R17	1/4"	12XX-04	1-piece	16.0	0.630	Full	14	N/A	8/1/23
5172-05	SAE100R17	5/16"	12XX-05	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5172-06	SAE100R17	3/8"	12XX-06	1-piece	20.0	0.787	Full	19	N/A	8/1/23
5172-08	SAE100R17	1/2"	12XX-08	1-piece	23.5	0.925	Full	23	N/A	8/1/23
5172-10	SAE100R17	5/8"	12XX-10	1-piece	27.7	1.091	Full	27	N/A	8/1/23
5172-12	SAE100R17	3/4"	12XX-12	1-piece	32.2	1.268	Full	31	N/A	8/1/23
5172-16	SAE100R17	1"	12XX-16	1-piece	41.1	1.618	Full	39	N/A	8/1/23
5192-04	SAE100R19	1/4"	12XX-04	1-piece	16.9	0.665	Full	16	N/A	8/1/23
5192-06	SAE100R19	3/8"	12XX-06	1-piece	21.0	0.827	Full	19	N/A	8/1/23
5192-08	SAE100R19	1/2"	12XX-08	1-piece	24.8	0.976	Full	23	N/A	8/1/23
5192-10	SAE100R19	5/8"	12XX-10	1-piece	27.8	1.094	Full	27	N/A	8/1/23
5192-12	SAE100R19	3/4"	12XX-12	1-piece	31.8	1.252	Full	31	N/A	8/1/23
5192-16	SAE100R19	1"	12XX-16	1-piece	40.6	1.598	Full	39	N/A	8/1/23
5201-08	N/A	1/2"	12XX-08	1-piece	24.5	0.965	Full	23	N/A	8/1/23
5205-24	4SH	1-1/2"	60XX-24	1-piece	58.0	2.283	Full	57	N/A	8/1/23
5210-24	N/A	1-1/2"	12XX-24	1-piece	59.4	2.339	Full	57	N/A	8/1/23
5220-04	Jack Line	1/4"	1220L-0404	1-piece	17.6	0.693	Full	16	N/A	8/1/23
5220-06	Jack Line	3/8"	1220L-0606	1-piece	22.2	0.874	Full	19	N/A	8/1/23

NOTES: Crimp scale settings are approximate.

The setting required to achieve the specified crimp diameter may be different depending on many factors including calibration and condition of the crimper. Crimp diameters specified must be met to ± 0.005 " (± 0.12 mm) to perform correctly on the indicated hose. All crimps should be positioned in the dies to achieve a full crimp covering the complete ferrule during crimp.

The picture at right demonstrates a representative location for all dies.

Crimp specs are valid for 90 days from revision date.

